

TSF-10,10F,11,11F




Bucket	Float	Disc	Bellows
Bimetal	Wafer	By-pass	Stainless steel
Connector	Side to side	Down to Up	Up to Down

■Features

1. The TSF-10・10F・11・11F can discharge condensate effectively without retention, and realize energy saving steam system without steam loss.
2. Incorporated thermostatic air vent discharges air inside the piping and shortens warming-up time.
3. By turning the cock, it is possible to meet various flow direction such as horizontal or vertical installation.
Flow direction can be switched easily without disassembly such as detaching the cover.
4. Since the main parts are installed on the cover, it is possible to disassemble the cover with the body installed on the piping so the inspection and parts replacement can be conducted easily.



TSF-10,11




TSF-10F,11F

■Specifications

Model		TSF-10	TSF-10F	TSF-11	TSF-11F
Nominal size		15A-25A			25A-50A
Application		Steam condensate			
Working pressure		TSF-1□□-5: 0.01-0.5 MPa TSF-1□□-10: 0.01-1.0 MPa TSF-1□□-21: 0.01-2.1 MPa			
Maximum temperature		220°C			
Material	Body	Ductile cast iron			
	Float	Stainless steel			
	Valve, valve seat	Stainless steel			
Connection		JIS Rc screwed NPT screwed	JIS 10K FF flanged JIS 20K FF flanged ASME150/300, ENPN25	JIS Rc screwed NPT screwed	JIS 10K FF flanged JIS 20K FF flanged ASME150/300, ENPN25

■Caution for Installation



Adjust direction of the name plate in no pressure condition after installation.

Fix the cock with spanner and loosen the nut. Turn the cock and adjust direction of the name plate to position "TOP" and "BOTTOM" signs on upside and downside respectively. Fix the cock with spanner and fasten the nut after adjustment.

* In case of Bottom to Top, Please apply that shorten the vertical piping before the trap to open and discharge easily of trap in the condition of using upward flow direction.


■ Dimensions (mm) and Weights (kg)

•TSF-11

Nominal size	d	L	A	A ₁	H	Weight
25A	Rc 1	190	244	147	186	9.9
32A	Rc 1-1/4	190	244	147	186	10.0
40A	Rc 1-1/2	205	244	147	186	10.2
50A	Rc 2	220	244	147	186	10.5


•TSF-11F

Nominal size	d	L	A	A ₁	H	Weight
25A	25	270	244	147	186	13.4
32A	32	270	244	147	186	14.1
40A	40	280	244	147	186	14.4
50A	50	290	244	147	186	15.5



■ Maximum Continuous Discharge Capacity Chart

•TSF-11, 11F



The discharge capacity shown in the charts on the above is the maximum value. In designing a system, select a steam trap with a sufficient safety factor (more than two times the regular level).